

COMPACT CURRENT TRANSFORMER FOR THE UMG 20CM, TYPE CT-20, CLASS 1

This current transformer can detect both operating and residual currents. It is suitable for use in a 3-phase circuit breaker. It is possible to plug together several current transformers of this series.



COMPACT CURRENT TRANSFORMER FOR THE UMG 20CM, TYPE CT-20 – TECHNICAL DATA

CURRENT TRANSFORMER, TYPE CT-20, CLASS 1

TYPE	MAX. OPERATING CURRENT in A	RESIDUAL CURRENT in mA	RATIO	MAX Ø OF PRIMARY CONDUCTOR in mm	DIMENSIONS in mm	WEIGHT in kg	PART NO.
CT-20	63 (with load)	10 ... 1000	700/1	7.5	approx. 27 x 46 x 23	0.05	1503082
ACCESSORIES							
Snap-on mounting for DIN rail EN 50022-35, suitable for type CT-20					approx. 41 x 14 x 27	approx. 0.1	0909010
Prefabricated connecting cable: 1.5 m with load (0.8 Ω) and spring terminal for operating current measurement							1503085

COMPACT CURRENT TRANSFORMER FOR THE UMG 20CM, TYPE CT-20 –
DIMENSIONAL DRAWINGS

